




Benefits

- Dimmable from 10-100% brightness
- Easily retrofit conventional fixtures with LED
- Tune light intensity to suit your environment or the time of day
- Up to 85% energy savings compared to halogen GU5.3

Application



| Model                | Item Description               | W   | PF  | lm  | lm/W | CRI | Beam Angle | Life (hrs) | Single Box (LxWxH)mm | Outer Box (LxWxH)mm | Packing Qty (PCS/CTN) |
|----------------------|--------------------------------|-----|-----|-----|------|-----|------------|------------|----------------------|---------------------|-----------------------|
| ER203080/dm-HRv00-NF | MR16 8W GU5.3 HR 2800K DIM 24D | 8.0 | 0.9 | 600 | 75   | 80  | 24°        | 25000      | 55*55*65             | 294*244*230         | 60                    |

| Application Conditions  |          |
|-------------------------|----------|
| IP                      | IP20     |
| Operating Temperature   | -20~40°C |
| Application Temperature | 25°C     |
| Storage Environment     | -25~50°C |

| Mechanical Properties |       |
|-----------------------|-------|
| Optical Material      | PC    |
| Housing Material      | PBT   |
| Finishing Colour      | White |

| Electrical Supply |    |
|-------------------|----|
| Voltage (V)       | 12 |
| AC/DC             | AC |

Dimensional Drawing

