

Technical Data Sheet



Product: ULTITEC 500 coverall

Light Protection Protective Coverall

Style NO: DD010 Standard Hooded Coverall

DD030 Collared Coverall

Material: Fabric: PPSB fabric in weight 35gsm

Zipper: Nylon on Polyester Braid Elastic: Neoprene Rubber (latex free)

Thread: Polyester

Color: White, Blue, Orange

Sizing: An appropriate size should be selected

to allow sufficient movement for the task

SIZE	CHEST (CMS)	HEIGHT (CMS)
S	84 - 92	162 - 170
M	92 - 100	170 - 176
L	100 - 108	176 - 182
XL	108 - 116	182 - 188
2XL	116 - 124	188 - 194
3XL	124 - 132	194 - 200
special larger sizes to order		

Application :

Civil Protection, Construction, Decorative Work, Food Processing&Packing

Approvals :

CE approved under PPE regulation EU 2016/425, Category I Module D Supervision: SGS United Kingdom, LTD. Notified Body Number: 0120

Design Feature :

3-piece hood; Elasticated wrist, ankle, and face opening; Fully elasticated waist; Ample Crotch; Zipper fastens to underside of chin; Storm Flap cover.

Storage and Disposal:

- Store in clean conditions in original packaging within the temperature range 15°C to 25°C (58°F to 78°F) and with relative humidity below 80%.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

Limitation :


Do not wash

Do not clean dry

Do not iron

Do not machine dry

Do not reuse



Packing: • 1 piece per PE bag

• 50 pieces per carton

