E8431CATV_SA 1 Gang CATV Socket, Sliver Satin





Main

ZENcelo
TV/FM/SAT socket
F connectors
CATV
Silver satin

Complementary

Device mounting	Surface	
	Flush	
Socket number	1 45° ground lug	
Number of gangs	1 gang	
Material	Polycarbonate: cover	
Bandwidth	5862 Hz	
Maximum insertion loss	1 dB	
Connections - terminals	F connectors: clamps terminal	
	Saddle terminal: clamps terminal	
	Inner: pillar terminal without pressure plate	
Width	87 mm	
Height	87 mm	
Depth	37.4 mm	

Environment

Livilorii		
Ambient air temperature for operation	-535 °C	
Relative humidity	095 %	
Environmental characteristic	No UV resistant	=
Standards	BS 3041	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3 cm	
Package 1 Width	8.72 cm	
Package 1 Length	8.72 cm	
Package 1 Weight	94.2 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	6	
Package 2 Height	15 cm	
Package 2 Width	19 cm	
Package 2 Length	6 cm	
Package 2 Weight	765 g	
Unit Type of Package 3	CAR	
Number of Units in Package 3	60	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 3 Height	21 cm	
Package 3 Width	32.5 cm	
Package 3 Length	50 cm	
Package 3 Weight	8152 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------