



| REV | DESCRIPTION | DATE |
|-----|-------------|------|
|-----|-------------|------|

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

|        |    |    |  |
|--------|----|----|--|
| A.W.G. | 12 | 10 |  |
| AMP.   | 35 | 50 |  |
  2. MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : YELLOW
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 12-10 A.W.G. ( 4-6 mm<sup>2</sup>)
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 1.00 mm

| Tolerance Unless Otherwise Specified |          |
|--------------------------------------|----------|
| 0 > 6 mm ± 0.20                      | ANGLE    |
| 6 > 18 mm ± 0.30                     | 0° REF ± |
| 18 > 30 mm ± 0.40                    | ±        |
| 30 > 75 mm ± 0.50                    | ±        |

|          |  |          |       |         |           |
|----------|--|----------|-------|---------|-----------|
| NAME     | VINYL-INSULATED (MOLDED) SPADE TERMINALS |          |       | UNIT    |           |
| PART NO. | SVY5-5@                                  | MATERIAL | ----- | APPROVE |           |
| NUMBER   | KA-96137-C                               | SCALE    | SHEET | PAGE    | CHECKED   |
| DATE     | 2007/02/01                               | 4/1      | 1-0   | 20F2    | DRAWN 張馨尹 |