



## HUSQVARNA T540 XP® II

Husqvarna T540 XP® is designed for the high-end top handle saw segment, targeting professional customers like full pro arborists, landscapers, garden contractors and utility services who need excellent performance in combination with the best ergonomics.



Individual grip size The top handle grip size can be set in three alternative sizes, to perfectly fit your hand.



Belt eye let: 2368 T540 XP®: 101086

Adjustable oil pump

your needs.

Adjustable oil pump makes it easy to set the chain lubrication according to

AutoTune: 1969 T540 XP®: 101086



## FEATURES

- AutoTune: 1969 T540 XP®: 101086
- Adjustable chain oil pump
- Interchangeable grip size, to perfectly fit your hand.
- Belt eye let: 2368 T540 XP®: 101086
- Quick-release air filter
- Auto return stop switch: 856 T540 XP®: 101086

Technical specifications	
DIMENSIONS	
Gauge	1.3 mm
Weight (excl. cutting equipment)	3.9 kg
ENGINE	
Cylinder displacement	37.7 cm <sup>3</sup>
Electrode gap	0.5 mm
Fuel consumption	480 g/kWh
Fuel consumption	0.87 kg/h
Fuel tank volume	0.341
Idling speed	3000 rpm
Maximum power speed	10200 rpm
Power output	1.8 kW
Spark plug	NGK CMR6H
Torque, max.	1.83 Nm
EQUIPMENT	
Bar mount	Small
Chain speed at max power	19.4 m/s
Chain speed at 133% of maximum engine power speed	25.8 m/s
Gauge	1.3 mm
Pitch	3/8"
Recommended bar length, max	40 cm
Recommended bar length, min	30 cm
Sprocket type	Spur 6
LUBRICANT	
Oil pump capacity Max	9 ml/min
Oil pump capacity Min	3 ml/min
Oil pump type	Adjustable flow
Oil tank volume	0.21
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	116 dB(A)
Sound power level, galanticed (EWY)	114 dB(A)
Sound power level, inclusived	104 dB(A)
VIBRATION	10100(1)
	2.1 / -2
Equivalent vibration level (ahv. eq) front handle	3.1 m/s <sup>2</sup>
Equivalent vibration level (ahv. eq) rear handle	3.2 m/s <sup>2</sup>
Engine Family FDA	
Engine Family EPA Engine Family CARB	JHVXS.0384AB JHVXS.0384AB
Exhaust emissions (CO average)	148.33 g/kWh
Exhaust emissions (CO average)	146.53 g/kWh 1066 g/kWh
Exhaust emissions (HC average)	42.15 g/kWh
Exhaust emissions (NOx average)	42.13 g/kWh
Exhaust emissions (NOX average)	4.50 g/ kwii
Exhaust emissions (CO average)	148.33 g/kWh
Exhaust emissions (CO FEL)	805 g/kWh
Exhaust emissions (CO average)	1066 g/kWh
Exhaust emissions (HC average)	42.15 g/kWh
Exhaust emissions (NOx average)	4.35 g/kWh
באומטא פווושאופו (ווטא מיפומעב)	7.50 g/ NWII
Exhaust emissions (CO average)	178.37 g/kWh
Exhaust emissions (CO average)	176.37 g/kWh 1050 g/kWh
Exhaust emissions (HC average)	40.81 g/kWh

## **PXM\_SPAREPARTS**



SPARK PLUG NGK CMR6H 531 00 86-15



FUEL FILTER FOR MOST OF OUR 574 44 45-02 HANDHELD PRODUCTS 503 44 32-01

PURGE BUBBLE 503 93 66-01