



### Main

|                                    |  |
|------------------------------------|--|
| Range                              | Spacial  |
| Accessory / separate part category | Mounting accessory   |
| Product or component type          | Mounting plate   |
| Device application                 | Multi-purpose  |
| Enclosure nominal dimensions       | -  |
| Mounting plate description         | Plain  |
| Range compatibility                | Spacial Spacial SF<br>Spacial Spacial SM<br>Spacial Spacial SFX<br>Spacial Spacial SMX |
| Device composition                 | 1 mounting plate<br>2 sliding shoes  |
| Quantity per set                   | Set of 1   |
| Material                           | Galvanised steel   |

### Complementary

|                            |  |
|----------------------------|--|
| Fixing mode                | By fixing brackets   |
| Maximum load               | 300 kg/m <sup>2</sup>  |
| Permanent permissible load | 500 Kg intermediate position<br>600 kg back of the enclosure |
| Height                     | Fixing centers: 1650 mm<br>Nominal: 1800 mm<br>Real: 1697 mm |
| Width                      | Fixing centers: 850 mm<br>Nominal: 1000 mm<br>Real: 896 mm   |
| Depth                      | 27 mm  |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 3 cm    |
| Package 1 Width              | 90 cm   |
| Package 1 Length             | 171 cm  |
| Package 1 Weight             | 34.2 kg |
| Unit Type of Package 2       | P2M     |
| Number of Units in Package 2 | 20      |
| Package 2 Height             | 80 cm   |
| Package 2 Width              | 200 cm  |
| Package 2 Length             | 120 cm  |
| Package 2 Weight             | 720 kg  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | No need of specific recycling operations   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|