



## 1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-2 GHz  
 1.2 NOMINAL IMPEDANCE: 75 OHMS  
 1.3 WORKING VOLTAGE: 300 VOLTS MAX.  
 1.4 PROOF VOLTAGE: 1000 VOLTS  
 1.5 VSWR: 1.1 MAX.@750 MHz  
 1.10 MAX.@1 GHz

## 2.0 MATERIALS

- 2.1 BODIES: BRASS PER JE-C3604  
 2.2 CENTER CONTACT: PHOSPHOR BRONZE JS-B3270  
 2.3 INSULATION: TEFLON PER ASTM D1487 AND ASTM D1710

## 3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

## 4.0 ENVIRONMENTAL

- 4.1 OPERATING TEMPERATURE RANGE: -40° C TO +85° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
4	CENTER CONTACT	PHOSPHOR BRONZE	1	GOLD
3	BODY	BRASS	1	NICKEL 100μ" MIN.
2	INSULATION	TEFLON	1	NONE
1	WASHER	BRASS	1	NICKEL 100μ" MIN.



APPROVED

by \_\_\_\_\_ DATE: \_\_\_\_\_

DRAWN		TOLERANCE		品名		56-05 T.G.N		日期	DATE	版次	REV.
Yoko		.X	±0.2	TITLE		\ROHS COMPLIANT (750)		04.13.07		A-0	
CHECK		.XX	±0.1	單位	UNIT	DWG.NO.	56-0008				
Monica		.XXX	±0.05					mm(In)			
APPROVAL		ANGLE	±5°	比例	SCALE						
Monica						6:1					