

FEATURES

- Low noise levels
- PBT Thermoplastic casing
- Square orientation
- Can be mounted in a horizontal and vertical position

RS PRO, 12 V dc, DC Axial Fan, 80 x 80 x 25mm, 68m³/h, 1.8W

RS Stock No.:541-5053



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Brought to you by RS PRO, a range of AC dual ball bearing axial fans offering a cost-effective cooling solution without sacrificing on quality or reliability. Provided are a robust die-cast aluminium frame and an AC shaded pole impedance protected motor, these fans are ideal for a multitude of applications.

General Specifications

Air Flow	40CFM
Fan Speed	3100rpm
Static Pressure	0.15in/H2O
Noise Level	35dB
Direction of Curve	Backwards
Frame	PBT, ULV94-0 plastic
Impeller	PBT, ULV94-0 plastic
Alarm Function	No
Applications	Server racks, Electrical cabinets and enclosures; Production Lines, Ceiling fan/ventilation Desktop computers, Motor engines (radiator in a car), Generators, Air compressors

Electrical Specifications

Motor	Brushless DC, Auto Cut off, Auto Restart, Polarity Protected
AC or DC Operation	DC
Power Consumption	1.8W
Supply Voltage	12VDC
Rated Voltage	12VDC
Maximum Current	180mA
Dielectric Strength	500VAC/min < 1mA
Insulation Resistance	10M ohm between lead wire and frame (500VDC)

Mechanical Specifications

Dimensions	80mm x80mm x25mm
Height	80mm
Width	80mm
Depth	25mm
Bearing Type	Ball
Weight	0.086Kg (0.19lbs)
Life Expectancy	60,000 hours (L10 at 45°C)

Operation Environment Specifications

Operating Temperature	-20°C to 75°C
Storage Temperature	-40°C to 80°C

Approvals

Compliance/Certifications	UL, cUL, TUV, CE, UL94-V0
----------------------------------	---------------------------



