

Product data sheet

Characteristics

SMX2200HV

APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 4U, 208V-230V, 8x C13+2x C19 IEC, SmartSlot, Extended runtime, Short depth



Overview

| | |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentation | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
| Lead time | Usually in Stock |

Main

| | |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Main Input Voltage | 208 V 230 V |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 208 V 230 V |
| Other Output Voltage | 208 V 220 V 240 V |
| Rated power in W | 1980 W |
| Rated power in VA | 2200 VA |
| Input Connection Type | IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British |
| Output connection type | 8 IEC 320 C13 2 IEC Jumpers 2 IEC 320 C19 |
| Number of rack unit | 4U |
| Cable length | 2.00 m |
| Number of cables | 1 |
| Battery type | Lead-acid battery |
| Provided equipment | CD with software Documentation CD Rack mounting support rails Smart UPS signalling RS-232 cable User manual USB cable |

Batteries & Runtime

| | |
|----------------------------------------|-----|
| Extended runtime | 1 |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |
| Number of battery replacement quantity | 1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-----------------------|---------------|
| Battery life | 3...5 year(s) |
| Battery charger power | 233 W rated |

General

| | |
|-------------------------------------|--------------|
| Number of power module | 1750 |
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Product web sub-family | Extended run |
| Redundant | No |

Physical

| | |
|---------------------|--------------|
| Colour | Black |
| Height | 43.2 cm |
| Width | 17.8 cm |
| Depth | 48.3 cm |
| Net weight | 38.56 kg |
| Mounting location | Front |
| Mounting preference | Lower |
| Mounting mode | Rack-mounted |
| Two post mountable | 1 |
| USB compatible | Yes |

Input

| | |
|----------------------|--------------------------------|
| Input voltage limits | 140...280 V |
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |

Output

| | |
|----------------------------------|---------------------------------|
| Harmonic distortion | Less than 5 % |
| Maximum configurable power in VA | 2200 VA |
| Maximum configurable power in W | 1980 W |
| Transfer time | 6 ms typical : 10 ms maximum |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |

Conformance

| | |
|------------------------|------------------------------------------------------------------------------------|
| Product certifications | CE[RETURN]CSA[RETURN]EAC[RETURN]IRAM[RETURN]RCM[RETURN]VDE |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|-------------------|
| Acoustic level | 55 dBA |
| Heat dissipation | 150 Btu/h |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0.00...15240.00 m |
| Relative humidity | 0...95 % |
| Storage Relative Humidity | 0...95 % |

Communications & Management

| | |
|---------------------|----------------------------------------------------------------------------------------|
| Control panel | Multifunction LCD status and control console |
| Emergency power off | Yes |
| Free slots | 1 |
| Control panel | LED status display with on line : on battery : replace battery and overload indicators |
| Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|-------------------|------------------------------------------------------------------------------------------------------------------|
| Surge energy rate | 645 J |
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 33 cm |
| Package 1 Width | 63.3 cm |
| Package 1 Length | 58.6 cm |
| Package 1 Weight | 47.73 kg |
| Pallet unit layers | 2 |
| Pallet layers | 4 |

Offer Sustainability

| | |
|-----------------------------|-----------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|-----------------------------------------------------------------------|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|-----------------------------------------------------------------------|