





Suitable for use in industrial and

Manufactured with a durable steel body

Supplied maintained and can be wired

LED Recessed Emergency Exit Sign

Description

The RS Pro 4W Recessed Emergency Exit Sign is suitable for use in both industrial and commercial applications. Supplied maintained, this fitting also has the option to wire as a non-maintained equivalent. This product has an emergency duration of 3 hours and is available with either Up (**253-9979**) and L/R (**253-9981**) arrow legend

Features

Range

253-9979	4W Emergency Recessed Exit Sign	
	with Up Arrow Legend	
253-9981	4W Emergency Recessed Exit Sign	
	Left & Right Arrow Legend	

non-maintainedIP20 for indoor use

and acrylic diffuser


commercial applications

Technical Specification

Wattage	4W	
Voltage	220-240V	
Frequency	50-60Hz	
Battery Chemistry	4.8V 1800mAh Ni-Cad	
Colour Temperature	6500K	
Emergency Duration	3 hours (Minimum)	
Indicators	Green, Battery Charge	
Material	Steel Body with Acrylic	
	Diffuser	
IP Rating	IP20	
Dimmable	No	
Light Source	Non-replaceable LED	
Lifespan	50,000hrs	
Standards	BS EN 60598-1	
	BS EN 50172:2004	

Dimensions

	Length	Height	Depth
253-9979	410mm	240mm	140mm
253-9981	410mm	240mm	140mm



No Serviceable parts

Contact your local authority for information concerning the correct disposal of your product