

EPT ADJUSTABLE CLICK WRENCH

- Durable and robust for industrial fastening applications.
- Adjustable torque wrench with a square drive. Bi-directional ratchet head.
- External dual scale (American & S.I.) Graduation collar on the torque handle.
- Easy to read laser marked scale.
- Built with a robust steel shaft with high corrosion resistance.
- Lightly knurled non-slip grip.
- 60 tooth ratchet (for EPT100i). 48 tooth ratchet (for models EPT250i - EPT750F).
- Positive lock with spring-loaded pull-down ring.
- Positive click can be heard and felt when torque is reached.
- This adjustable click wrench is ideal for field service, maintenance or production environments.
- The preferred and certified ranges of these tools are in accordance with the requirements of ISO 6789 (+/- 4% of indicated setting).



Torque Ranges

Models	Item #	Grad. Scale		Grad. Scale	Drive Size	
		American	S.I.			American
EPT100i	280050	20 - 100 lbf.in	2.8 - 11.9 N.m	0.5 lbf.in	0.1 N.m	1/4" Sq. Dr.
EPT250i-D	280033	50 - 250 lbf.in	6.2 - 28.8 N.m	1 lbf.in	0.1 N.m	1/4" Sq. Dr.
EPT250i-A	280034	50 - 250 lbf.in	6.2 - 28.8 N.m	1 lbf.in	0.1 N.m	3/8" Sq. Dr.
EPT75F	280035	15 - 75 lbf.ft	23.7 - 105.1 N.m	0.5 lbf.ft	0.5 N.m	3/8" Sq. Dr.
EPT150F	280036	10 - 150 lbf.ft	20.3 - 210.1 N.m	1 lbf.ft	1 N.m	1/2" Sq. Dr.
EPT250F	280037	30 - 250 lbf.ft	47.4 - 345.7 N.m	2 lbf.ft	2 N.m	1/2" Sq. Dr.
EPT400F	280038	80 - 400 lbf.ft	142.3 - 559.2 N.m	2.5 lbf.ft	2.5 N.m	3/4" Sq. Dr.
EPT550F	280039	110 - 550 lbf.ft	183 - 779.5 N.m	2.5 lbf.ft	5 N.m	3/4" Sq. Dr.
EPT750F	280040	150 - 750 lbf.ft	237.2 - 1050.6 N.m	5 lbf.ft	5 N.m	1" Sq. Dr.

Note! After being used, adjustable click torque wrenches should be turned back to minimum scale value. This helps to preserve the springs and ensures a longer product life cycle with high precision.