

- SUPERIOR WET + DRY VACUUMING POWER**
- HIGH CAPACITY + HEAVY DUTY**
- EFFECTIVE WATER + DUST SEPARATION**

# SWD

**26 6S/7P    33 6S/7P**



- High Performance Suction Levels**
- Superior and Effective Wet + Dry Operation**
- Higher Productivity + Efficiency**
- Industrial Durability + Reliability**
- Convenient + User Friendly**
- Long Term Economy + Value**

# Construction + Features

The **SWD** series **26 6S/7P** and **33 6S/7P** are high performance industrial vacuum cleaners for heavy duty + large volume applications, with high suction and the **SWD** separator with wet + dry cyclonic barrier system for improved liquid and dust handling performance, with no filter change required. They provide very high productivity + efficiency, while discharging is convenient due to the drainage hose and tiltable tanks.



Powerful 2600W and 3300W maximum suction strength with 2 x 1300W or 3 x 1100W individually switchable motors and 2-stage fans giving maximum air flow of 435 m<sup>3</sup>/h and 645 m<sup>3</sup>/h for high productivity.  
Bypass cooling protection prolongs motor operating life for long usage.




6S: Heavy duty stainless steel



7P: Heavy duty polypropylene, chemical resistant

High capacity 89-107 (gross) / 67-74 (nett) litres, highly durable tanks, allow for large amounts of liquids and materials to be continuously collected on the job.



High efficiency **SWD** cyclonic separator system circulates liquids and coarse dusts down to the tank. An external float valve blocks liquid entry to the filter compartment.  
Filter cartridge is partitioned above the separator, avoiding chokage.  
Effective for concurrent and mixed wet/dry use, eliminates use of bags.



Robust yet light steel frame ensures strong support.  
Large rugged wheels and castors for stable mobility over indoor and outdoor surfaces.  
Optional accessory basket KSKX02879 (SWD26/33 6S only)



Integrated drain hoses for quick and convenient discharge of liquid wastes.



Fully tilting tank mechanism with control handles easily discharges all liquids or solids.



SPECIFICATIONS	SWD26 6S / 7P	SWD33 6S / 7P
Motor Power [W]	2 x 1300	3 x 1100
Voltage [V]/[Hz]	220-240/50-60	220-240/50-60
Fan type	2-stage	2-stage
Motor cooling	By-pass	By-pass
Airflow (max) [m <sup>3</sup> /h]	435	645
Vacuum (max) [Pa]	26460	24130
Tank capacity (app. gross) [ltr]	89 / 107	89 / 107
Tank capacity (app. nett) [ltr]	67 / 74	67 / 74
Liquid overflow control	External shut-off valve	External shut-off valve
Discharge system	Drain hose & tilt tank	Drain hose & tilt tank
Sound level [dB]	74.9	77.2
Dimensions (l x w x h) [cm]	70 x 57 x 116	70 x 57 x 114
Weight (w/o accessories) [kg]	33 / 32	34 / 33

STANDARD ACCESSORIES	SWD26 6S / 7P	SWD33 6S / 7P
	Ø 40mm	Ø 50mm
Suction hose assembly, 2.5 m	KSTBFX01166	KS02779
Suction wand stainless steel (set of 2 / 3)	KS00580	KS02364
Wet floor wheeled pick-up nozzle	KS03893	KS03893/50
Dry floor wheeled pick-up nozzle	KS03892	KS03892/50
Straight PVC extension tubes (set of 2)	-	KS00513
Round dusting brush	KS06295	KS00517
Triangle bulk pick-up tool	-	KS00518
Crevice nozzle	KS00003	KS00516

Units are equipped with full range of standard wet and dry industrial cleaning tools. Other options also available for both high reach and special cleaning applications.



FILTER OPTIONS	[ ● standard, ○ optional ]
Polyester filter cartridge (wet / dry)	● KSKX07063
Microfibre filter bags, disposable (set of 5)	○ KS02875-C
HEPA filter cartridge	○ KS02995
Filter cartridge holder (for HEPA filter)	○ KS02855



### Other Kinetix models:

- Wet/dry cleaning
- Cleanroom & high filtration
- Hazardous dust & health
- Explosion proof & safety
- Industrial high capacity

