



ENGLISH

Datasheet


RS PRO 4 pairs U/FTP Cat6A LSZH

Stock No: 2097611

LN-A0423AN6A-LIS-077-GY-100



Cross Section



1	Outer jacket
2	AL/Polyester
3	Insulation
4	Conductor
5	Drain wire

Physical characteristics

Structure	Construction	U/FTP
	Number of Pairs	4
Conductor	AWG	23 AWG
	Conductor material	Solid bare copper
	Conductor dimension	0.566±0.02 mm
Insulation	Insulation material	Foam PE
	Insulation dimension	1.28±0.05 mm
	Number colour (Stripe marking)	A.White/Blue(Stripe) & Blue B.White/Orange(Stripe) & Orange C.White/Green(Stripe) & Green D.White/Brown(Stripe) & Brown
Cabling	Twisting lay length	≅ 30mm
	Cabling lay length	≅ 200mm
Filler	Filler material	N/A
Shield	Individual shield & material (Each Pair)	AL/Polyester,AL-foil facing outside
	Primary overall shield braid&material	N/A
	Shield coverage Min.	N/A
	Drain wire	1/26AWGTinned copper
Outer jacket	Outer jacket material	LSZH
	Outer jacket thickness (Min.)	0.4 mm
	Overall nominal dimension	6.9±0.3 mm
	Outer jacket rip cord	N/A
	Outer jacket colour	Gray (RAL7037)
Mechanical characteristics	Operating temperature range	-20 °C ~ +75 °C
	Cold bend	No crack (@ -20°C x 4hrs)
	Max. recommended pulling tension	80 N
	Outer jacket tensile strength	≅ 9 MPa
	Outer jacket elongation	≅ 100%
	Outer jacket aging condition	(100±2) °C x 168 hrs
	After aging, Tensile strength	≅ 70% of Unaging
After aging, Elongation	≅ 50% of Unaging	
Electrical characteristics	Nom. mutual capacitance	≅ 5.6 nF/100m (@1kHz)
	Pair to ground capacitance unbalance	≅ 330 pF/100m
	Nominal velocity of propagation	65%
	Max. delay skew	45 ns/100m
	Max. conductor DC resistance	9.5 Ω/100m (@ 20 °C)
	Conductor resistance unbalance	≤2% (@ 20 °C)
	Resistance unbalance between pairs	≤5% (@ 20 °C)
	Min. insulation resistance	5000 MΩ·m
Max. operating voltage - UL	300 V	

Performance (Test Length : 100m)

Electrical characteristics:

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB Min)	PSNEXT (dB Min)	Return loss (dB Min)	ACR-F (dB Min)	PSACR-F (dB Min)	PD (ns/100m)
4	3.8	66.3	63.3	23.0	56.0	53.0	552.0
8	5.3	61.8	58.8	24.5	49.9	46.9	546.7
10	5.9	60.3	57.3	25.0	48.0	45.0	545.4
16	7.5	57.2	54.2	25.0	43.9	40.9	543.0
20	8.4	55.8	52.8	25.0	42.0	39.0	542.0
25	9.4	54.3	51.3	24.3	40.0	37.0	541.2
31.25	10.5	52.9	49.9	23.6	38.1	35.1	540.4
62.5	15.0	48.4	45.4	21.5	32.1	29.1	538.6
100	19.1	45.3	42.3	20.1	28.0	25.0	537.6
200	27.6	40.8	37.8	18.0	22.0	19.0	536.5
250	31.1	39.3	36.3	17.3	20.0	17.0	536.3
300	34.3	38.1	35.1	17.3	18.5	15.5	536.1
400	40.1	36.3	33.3	17.3	16.0	13.0	535.8
500	45.3	34.8	31.8	17.3	14.0	11.0	535.6

Frequency (MHz)	Input Impedance upper limit	Input Impedance lower limit
	(Ω)	(Ω)
4	115.2	86.8
8	112.6	88.8
10	111.9	89.4
16	111.9	89.4
20	111.9	89.4
25	112.9	88.5
31.25	114.1	87.7
62.5	118.3	84.5
100	121.9	82.0
200	125.7	79.6
250	128.8	77.6
300	131.5	76.0
400	131.6	76.0
500	131.6	76.0

Note:

*Test ambient temp. is 20°C

* Cable that meet the requirements of the characteristic impedance are not required to be measured for return loss; alternately cables that meet the return loss requirements are not required to be measured for characteristic impedance.

* Cable measurement precautions

Mutual capacitance, capacitance unbalance, characteristic impedance, return loss, insertion loss, SRL, NEXT loss, ACRF, TCL, and TCTL measurements and calculations shall be performed on cable samples of 100 m (328 ft) removed from the reel or packaging. The test sample shall be laid out along a non-conducting surface, loosely coiled, or supported in aerial spans, and all pairs shall be terminated according to the specific requirements of this annex. Other test configurations are acceptable if correlation to the reference method has been verified. In case of conflict, the reference method (100 m, off-reel, resistor terminated) shall be used to determine conformance to the minimum requirements of this Standard.

Description

- Rated temperature: 75°C
- Reference standard: IEC 61156-10&ISO/IEC 11801-1,
- Product standard certification:CPR
- Flame test: EUROCLASS Dca
- Stranded bare copper conductor
- Colour-coded PE insulation
- LSZH jacket

Application

- 100Base-T4
- 100Base-TX
- 100VG-AnyLAN
- 1000Base-T
- 1000Base-TX
- 155Mbps ATM
- 622Mbps ATM
- 10 Gb Ethernet

Marking

HUAXUN LAN CABLE 4PR 23AWG U/FTP EUROCLASS Dca-s2, d2, a1 CAT6A LSZH 75°C
YYYYMMDDJJNN *****M

Note:

- 1.The jacket shall be used black jet print marking except white color on black jacket.
- 2.YYYYMMDDJJNN-Batch number.
- 3.*****- sequential meter marking with 1m interval.
- 4.Marking height :3+/-0.3mm,width 2+/-0.3mm.