

Datasheet

ENGLISH

PVC 10m Long Blue Flexible Tube Reinforced

RS Stock number 339-6360

INDUSTRIAL LAYFLAT HOSE - LH series

Special Features

- Made from Cadmium free materials
- Resistance to a wide range of chemicals (see Chemical Resistance Table)
- Silicone free
- Abrasive resistant
- Good flexibility
- Long service life
- Minimal electrical conductivity
- Tough, puncture-proof
- Fast transfer of liquids
- Unaffected by the elements







ENGLISH

CODEFLAT INDUSTRIAL LAYFLAT

(U.K. And European Sizes)

			Weight	Burst Pressure @ 20℃	
Product	Sk	18	per coil	Bar	PSI
Ref	I.D.	Wall	kgs	3:1 Safety Factor	
LH10	26	1.5	16	21	298.2
LH 125	33	1.6	20	21	298.2
LH 15	40	1.6	21	15	213
LH 20	52	1.65	29	13.5	191.7
LH 25	65	1.7	40	12	170.4
LH 30	77	1.8	57	12	170.4
LH 40	103	1.9	75	12	170.4
LH 50**	128	2	100	9	127.8
LH 60	153	2.1	125	9	127.8
LH 80	207	2.3	193	9	127.8
LH 100**	257	2.7	270	7.5	106.5
LH120**	308	2.7	290	6	85.2

CODEFLAT MEDIUM DUTY INDUSTRIAL LAYFLAT

(U.K. And European Sizes)

		Weight	Burst Pressure @ 20°C	
Product	Size	percoil	Bar	PSI
Ref	LD.	kgs	3:1 Safety Factor	
LHM075	3/4"	17.0	38.7	569
LHM10	1*	22.5	33.8	498
LHM125	1 1/4"	25.0	29.0	427
LHM15	1 1/2"	30.0	24	356
LHM20	2*	41.0	24	356
LHM25	2 1/2"	58.0	24	356
LHM30	3*	70.0	24	356
LHM40	4*	1.05.0	24	356
LHM60	6*	1.60.0	11.6	171

CODEFLAT HEAVY DUTY INDUSTRIAL LAYFLAT

(U.K. And European Sizes)

			Weight	Burst Pressure @ 20°C	
Product	9	28	per coil	Bar	PSI
Ref	LD.	Wall	kgs	3:1 Safety Factor	
LHD15	40	1.8	30	31.5	447.3
LHD20	52.5	2	42	31.5	447.3
LHD25	66	2.1	55	31.5	447.3
LHD30	78.5	2.1	66	27	383.4
LHD40	104	2.5	102	27	383.4
LHD60	155	2.7	165	21	298.2

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.