



Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Socket additional information	Shuttered
Colour tint	Silver bronze

Complementary

Communication network category	Voice: 3 Data: 5e
Insulation resistance	>= 200 MOhm
Number of gangs	2 gangs
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate plastic part
Device mounting	Surface Flush
Width	87 mm
Height	87 mm
Depth	36 mm
Embedding depth	30.2 mm

Environment

AWG gauge	AWG 34...AWG 23 (4 twisted pair cables)
Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	118.43 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm

Package 2 Length	19 cm
Package 2 Weight	1.147 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	11974.4 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins