

FEATURES

- High impact textured low profile aluminium alloy cover
- Warp proof self-extinguishing UL approved PVC base
- Maximum service temperature of 85°C
- Self-adhesive tape applied to the PVC base for quick easy installation

RS PRO Grey Floor Trunking, W50 mm x D9.8mm, L1m, Aluminium Alloy (Lid), PVC (Base)

RS Stock No.: 880-6865



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From RS Pro, a range of aluminium floor cable trunking designed for mounting on floors for routing low voltage and signal wires in high traffic areas. This trunking consists of a warp proof self-extinguishing PVC inner rail and a low profile high impact decorative convex extruded aluminium top cover. The PVC base is self-adhesive and the aluminium cover is securely dovetails over the top. All models are highly reliable and excellent quality.

General Specifications

Trunking/Chain Type	Floor Trunking
Material	Aluminium Alloy (Lid), PVC (Base)
Colour	Grey
Fire Behaviour	Self-extinguishing
Applications	Offices and indoor work spaces, at various lengths, Electrical workshops, Schools, Hospitals, Hotels and anywhere with customers, walking amongst cables

Mechanical Specifications

Length	1m
Width	50mm
Depth	9.8mm

Operation Environment Specifications

Operating Temperature Range	Maximum 85°C
Maximum Service Temperature	85°C

Approvals

Standards Met

RoHS Compliant, UL 94 V-0

