


SPC-FODS.DWB

- 80"±3"

ALL RIGHTS RESERVED. NO WHETHER IN WHOLE OR IN WITHOUT THE EXPRESS WRITECHNOLOGY.

NO PORTION OF THIS PUBLICATION.			REVISIONS	- F	), SPC—FD05	* Eff &	:tivee: 7/8/0:	2 * PCP	00C. NO. 59C-FD05 + Effectives 7/8/D2 + DCP No. 1308
IN PART CAN BE REPRODUCED WRITTEN CONSENT OF SPC	DCP # REV	REV	DESCRIPTION	DRAWN	DRAWN DATE CHECKD DATE APPRVD DATE	CHECKD	DATE	APPRVD	DATE
	2011	٨	Released	ΔN	12/18/08 JWM 12/18/08 JWM 12/18/08	MWL	12/18/08	JWM	12/18/08





0

0 ٥

## NOTES:

1. CORDAGE: SJT, 14AWG / 3C, UNSHIELDED, CEE COLOR CODE, TEMP. RATING 60°C,

RATING: 125V 15A, JACKET COLOR: BLACK 2. PLUG: NEMA 5-15P 3. CONNECTOR: IEC 60320 C-13

4. APPROVALS: UL, cUL

	DEVER IN CONNECTION THEREWITH,	NDED USE AND ASSUME ALL RISK AND	TERMINE THE SUITABILITY OF THE PRODUCT		AND TECHNICAL INFORMATION CONTAINED	
	PURPOSES ONLY.	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE				I OLEXANCEO:
Jeff McVicker			Jeff McVicker	CHECKED BY:	Jason Nash	DRAWN DI:
12/18/08		D.A.T.E.	12/18/08	DATE:	12/18/08	DAIL;
SCALE: NIS		•	A SPC	DATE: SIZE DWG. NO.		DATE: URAWING HILE:
U.O.M.: INCHES [mm]			SPC13292	ELE	Power Cord	
SHEET: 1 OF		•	11J3566.dwg   ,	ELECTRONIC FILE   F		

> ₽