



Main

Range	Pieno
Product or component type	Switch
Switch application	Panic button
Cover frame colour tint	White

Complementary

Device mounting	Surface Flush
Wiring device mounting	Flush Surface
Switch function	Switch
Rated current	3 A at 24 V DC
Local signalling	Panic button: push-flat dolly, key reset (red)
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: button Polycarbonate: reset key
Clamping connection capacity	1 x 2.5 mm ² for solid cable(s) 1 x 1.5 mm ² for stranded cable(s)
Embedding depth	34 mm
Width	87 mm
Height	87 mm
Depth	34 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	75.85 g
Unit Type of Package 2	CAR
Number of Units in Package 2	60
Package 2 Height	21 cm
Package 2 Width	32.5 cm
Package 2 Length	50 cm
Package 2 Weight	5074.8 g

Unit Type of Package 3	PAL
Number of Units in Package 3	1200
Package 3 Height	86 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	108020 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------