


Product data sheet

Specifications



CONNECTOR 32A FUSE 10X38

KSB32CF5

Main

Range of product	Canalis
Range compatibility	KS busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunkingplug-in
[Ie] rated operational current	32 A at 35 °C
Protection type	fuse isolator: for gG cylindrical fuse, size 10 x 38 mm - 25 A conforming to NF fuse isolator: for aM cylindrical fuse, size 10 x 38 mm - 32 A conforming to NF
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO32 6 mm ² flexible Cable clamp terminal - ISO32 10 mm ² rigid
Door/Cover opening side	Front
Tap-off unit disconnection mode	By drawing out
Standards	IEC 61439-1 IEC 61439-6
Body material	Plastic
Width	135 mm
Depth	153 mm
Height	175 mm
Net weight	0.6 kg

Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	644.5 g
Package 1 Height	15.5 cm
Package 1 width	16.8 cm
Package 1 Length	18.3 cm
Unit Type of Package 2	P12
Number of Units in Package 2	119
Package 2 Weight	89.241 kg
Package 2 Height	79 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------