

FEATURES

- The supply voltage rating is 24VAC/24VDC
- 1C/O SPDT contact configuration with relay output 50mA
- 6-digit LED display
- Supports both, NPN and PNP sensors
- Inputs for capacitive and proximity sensors and an encoder supported
- Manual and automatic reset options
- 2 millisecond to 250 millisecond adjustable filter for pause, reset and start input parameters

RS PRO SPDT Timer Relay -, 1 Contacts, One Shot, Panel Mount

RS Stock No.: 808-6623



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO single-function timer relay performs the function of providing a one-shot delay in the range between 2 milliseconds and 250 milliseconds. It is a compact digital equipment with high precision and accuracy to suit a wide variety of applications. This can be installed into new and existing applications without much hassle.

General Specifications

Switch Configuration	SPDT
Mode of Operation	One-shot
Contact Configuration	SPDT
Number of Timer Functions	Single
Number of Contacts	1
Time Increment	Hours, Minutes, Seconds
Time Delay	Single, 2 milliseconds and 250 milliseconds
Applications	Textiles, Chemical industry, Mining, Irrigation, Raw material handling, Food and beverages, Industrial process control

Electrical Specifications

Power Supply	External
Supply Voltage	24V ac/dc
Maximum Voltage	24VAC/DC
Current Maximum	5A
Relay Output	1C/O SPDT contact configuration with relay output 50mA
Contact Material	Silver Nickel

Mechanical Specifications

Mounting Type	Panel
Depth	48mm
Width	48mm
Length	95.5mm

Operation Environment Specifications

Maximum Operating Temperature	50°C
Minimum Operating Temperature	0°C

Protection Category

IP Rating	IP20, IP65
-----------	------------

Approvals

Compliance/Certifications	CE, RoHS
---------------------------	----------



