

Torque Limiting Screwdrivers

Standard Models



- Standard product calibrated right hand only. Left hand calibration on request.
- Choice of adjustable models with precision micrometer scale or factory preset models.
- U.S. Standard or metric scales
- Precision micrometer scale (adjustable models) calibrated in inch-ounces or inch-pounds. Metric models: cm-kg.
- Easy-release bit holders securely retain bits during operation while permitting easy removal.
- Anti-backlash design for repeatability.
- Meets or exceeds ASME B107.14M and ISO 6789 specifications.
- Adjustable model accuracy is $\pm 6\%$ of setting, starting at 20% of full scale to full scale. Right hand only.

Adjustable Models

Model No.	Range	Collar Color	Increments	Hex Drive	Weight	
					lbs.	kg.
U.S. Standard						
TS-100	20-100 in.-oz.	Black	2 in.-oz.	1/4 Female	.50	.23
TS-30	6-30 in.-lb.	Red	1 in.-lb.	1/4 Female	.50	.23
TS-35	6-36 in.-lb.	Blue	1 in.-lb.	1/4 Female	.50	.23

Metric

TS-3M*	.7-3.5 Nm	Gold	.1 Nm	1/4 Female	.50	.23
--------	-----------	------	-------	------------	-----	-----

If calibration certification is required, request at time of purchase (extra charge).

Preset Models (Preset models are designed for highly repetitive assembly line operations.)

Model No.	Range				Hex Drive
	in.-oz.	in.-lb.	Nm	cm-kg	
TS-SN-1	20-150	1.5-10	.15-1.1	1.5-12	1/4 Female
TS-SN-2	128-640	8-40	1-4.5	9-45	1/4 Female

If calibration certification is required, request at time of purchase (extra charge).

NOTE: When ordering preset tools, specify desired torque setting.



TS-30

TS-SN-1

Distributed by : **All-Spec Industries**
Wilmington, NC

Ph: 800-537-0351
Fx: 800-379-9903

Web: www.all-spec.com
Email: sales@all-spec.com

Torque Limiting Screwdrivers

Standard Model Accessories & Kits



Hex Bits



Part No.	Hex Size	Cap Screw Size	Set Screw Size	Flathead Screw Size
185-000X	050	0	3,4	1,2
185-00X	1/16	1	5,6	3,4
185-0X	5/64	2,3	8	5,6
185-1X	3/32	4,5	10	8
185-9X	7/64	6	-	-
185-2X	1/8	-	1/4	10
185-10X	9/64	8	-	-
185-3X	5/32	10	5/16	1/4
185-4X	3/16	1/4	3/8	-

Phillips Bits



Part No.	Point Size	Screw Size
446-0X	0	0,1
446-1X	1	2,3,4
446-2X	2	5,6,7,8,10
440-3X	3	12,14

Screwdriver Bits



Part No.	Blade Width	Blade Thickness	Screw Size
445-00X	.134	.028	2,3
445-0X	.155	.030	3,4
445-10X	.185	.034	4,5
445-20X	.214	.036	5,6
445-30X	.250	.040	6,8

Square Drive Adapter



Part No.	Description
44-71-B	1/4 Hex to 1/4 Square.

Bit Holders



Part No.	Square Drive (in.)	Female Hex (in.)	Description
825	1/4	1/4	
M-825	1/4	1/4	Magnetic

SAE Size Sockets



Part No.	Square Dr. (in.)	Hex Opening (in.)
1108	1/4	1/4
1110	1/4	5/16
1112	1/4	3/8
1114	1/4	7/16

Metric Size Sockets

Part No.	Square Dr. (in.)	Hex Opening (mm)
6mm11	1/4	6mm
7mm11	1/4	7mm
8mm11	1/4	8mm
10mm11	1/4	10mm

Miniature Bit Holders



Part No.	Description
HW-19	To adapt miniature accessories for use in standard models. See page 11 for accessories.

Kit No. KT-100

Range 20-100 in.-oz. 20 piece

Qty.	Description
1	Adj. torque screwdriver 1/4" fm. hex
1	Torque screwdriver bld. .000
1	Torque screwdriver bld. .100
1	Hex socket 3/32"
1	Hex socket 7/64"
1	Hex key .028
1	Hex key .035
1	Screwdriver hex bit .050
1	Screwdriver hex bit 1/16"
1	Screwdriver hex bit 5/64"
1	Screwdriver bld. torque screw SZ. 2, 3
1	Screwdriver bld. torque screw SZ. 4, 5
1	Phillips bld. torque screw SZ. 0, 1
1	Phillips bld. torque screw SZ. 2, 3, 4
1	Adapter 1/4" drive
1	Bit holder mini. torque
1	1/4" Dr. reg. socket 1/8"
1	1/4" Dr. reg. socket 3/16"
1	Plas/case
1	Insert

Kit No. KT-30

Range 6 to 30 in.-lb. 24 piece

Qty.	Description
1	Adj. torque screwdriver 1/4" fm. hex
1	Torque screwdriver bld. .100
1	Hex socket 7/64"
1	Hex key .035
1	Screwdriver hex bit .050
1	Screwdriver hex bit 1/16"
1	Screwdriver hex bit 5/64"
1	Screwdriver hex bit 3/32"
1	Screwdriver hex bit 1/8"
1	Screwdriver hex bit 5/32"
1	Screwdriver bld. torque screw SZ. 2, 3
1	Screwdriver bld. torque screw SZ. 4, 5
1	Screwdriver bld. torque screw SZ. 5, 6
1	Screwdriver bld. torque screw SZ. 6, 8
1	Phillips bld. torque screw SZ. 0, 1
1	Phillips bld. torque screw SZ. 2, 3, 4
1	Adapter 1/4" drive
1	Bit holder mini. torque
1	1/4" Dr. reg. socket 1/8"
1	1/4" Dr. reg. socket 3/16"
1	1/4" Dr. reg. socket 1/4"
1	1/4" Dr. reg. socket 5/16"
1	Plas/case
1	Insert

Kit No. KT-130

Range 20 in.-oz. to 30 in.-lb. 43 piece

Qty.	Description
1	Adj. torque screwdriver 1/4" fm. hex
1	Adj. torque screwdriver 1/4" fm. hex
1	Torque screwdriver bld. .080
2	Torque screwdriver bld. .100
1	Hex socket 3/32"
2	Hex socket 7/64"
1	Hex key .028
2	Hex key .035
2	Screwdriver hex bit .050
2	Screwdriver hex bit 1/16"
2	Screwdriver hex bit 5/64"
1	Screwdriver hex bit 3/32"
1	Screwdriver hex bit 1/8"
1	Screwdriver hex bit 5/32"
2	Screwdriver bld. torque screw SZ. 2, 3
2	Screwdriver bld. torque screw SZ. 4, 5
1	Screwdriver bld. torque screw SZ. 5, 6
1	Screwdriver bld. torque screw SZ. 6, 8
2	Phillips bld. torque screw SZ. 0, 1
2	Phillips bld. torque screw SZ. 2, 3, 4
1	Phillips bld. torque screw SZ. 4, 6, 7, 8, 10
2	Adapter 1/4" drive
2	Bit holder mini. torque
1	1/4" Dr. reg. socket 1/8"
1	1/4" Dr. reg. socket 5/32"
2	1/4" Dr. reg. socket 3/16"
1	1/4" Dr. reg. socket 1/4"
1	1/4" Dr. reg. socket 5/16"
1	Plas/case
1	Insert



CAUTION: 1. Under normal use, periodic recalibration may be necessary to ensure accurate readings and applied torque.
2. FOR EXTENDED SPRING LIFE, RETURN TO LOWEST SETTING AFTER EACH USE.