



ENGLISH

Datasheet

Stock No.184-5598

RS PRO Capacitive Sensor



Specifications:

Mounting: Non flush
Rated distance Sn: 8mm(adjustable)
Assured distance Sa: 0...6.4mm
Shape size: M18*91.5mm
Output way: AC2 wires
Output status: NO
Supply voltage: 20...250 VAC
Standard target: Fe18*18*1t
Switch point offset[%/Sr]: $\leq \pm 20\%$
Hysteresis range [%/Sr]: 3...20%
Repeated error: $\leq 3\%$
Load current: $\leq 300\text{mA}$
Residual voltage: $\leq 10\text{V}$
Current consumption: $\leq 3\text{mA}$
Protection circuit:
Output indicator: Yellow LED
Ambient temperature: $-25^{\circ}\text{C} \dots 70^{\circ}\text{C}$
Ambient humidity: 35-95%RH
Switch frequency: 15 Hz
High pressure resistance: 1000V/AC 50/60Hz 60s
Insulation resistance: $\geq 50\text{M}\Omega(500\text{VDC})$
Vibration resistance: Complex amplitude 1.5mm 10...50Hz(2H per X,Y,Z direction)
Protection degree: IP67
Housing material: Nickel-copper alloy
Connection: M12 connector

Features:

- ◆ Be able to detect both metal and nonmetal objects;
- ◆ Be able to detect various media via nonmetallic container;
- ◆ Reliable liquid level detecting;

25/03/2019