



Main

Range	ZENcolo
Product or component type	Switch
Load type	Fluorescent lamp Resistive Inductive Incandescent lamp
Colour tint	Silver bronze
Cover frame colour tint	Silver bronze

Complementary

Device mounting	Flush Surface
Switch function	2-way
Rated current	16 AX at 250 V AC 50/60 Hz 20 A
Local signalling	Mechanical indicator (amber)
Number of gangs	2 gangs
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	31 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 IEC 60669-1 GB 16915.1 SS 227-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	148.26 g
Package 1 Height	3.5 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile