

## Datasheet

ENGLISH


# RS PRO, 12 V dc, 2000 gcm, Brushed DC Geared Motor, Output Speed 200 rpm

Stock No: 834-7596



## Specifications:

Output Speed	200 rpm
Supply Voltage	12 V dc
Maximum Output Torque	2000 g.cm
DC Motor Type	Brushed
Shaft Diameter	6mm
Power Rating	12.8 W
Gearhead Type	Spur
Length	81.6mm
Width	37mm
Current Rating	1.42 A
Weight	312g



Operating relative humidity 20% ~ 85%  
 Operating temperature range -10°C ~ +60°C

Ratio	L
50:1	24.5mm

Gearbox Housing material	Metal
Backlash at no-load	< 2°
Bearing at output	Sleeve bearings
Radial load (10mm from flange)	< 1 kgf
Shaft axial load	< 0.7 kgf
Shaft press fit force max	< 20 kgf
Radial play of shaft	< 0.05mm
Thrust play of shaft	< 0.35mm

Reduction Ratio	Rated tolerance Torque	Max momentary Tolerance Torque	Efficiency
1/30	2 kgf-cm Max.	6 kgf-cm	73%

Reduction Table RPM	4.5v	6v	9v	12v	15v
SUPPLY VOLTAGE					
834-7596	75	100	150	200	250

Note: Motor speeds may vary by (+) or (-) 10%