



Main

| | |
|---------------------------|----------------------|
| Range of product | Harmony XAC |
| Product or component type | Head for push-button |
| Component name | XACA |

Complementary

| | |
|---------------------------------------|--|
| Marking | Unmarked |
| Operator additional information | Booted |
| Cap/operator or lens colour | Black |
| Product compatibility | XACA.. |
| Mounting location | Front of enclosure |
| Sale per indivisible quantity | 10 |
| Standards | CSA C22.2 No 14 UL 508 IEC 60204-32 IEC 60947-5-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn conforming to IEC 60068-2-27 |
| Overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Net weight | 0.01 kg |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.200 cm |
| Package 1 Width | 3.000 cm |
| Package 1 Length | 3.000 cm |
| Package 1 Weight | 9.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 4.000 cm |
| Package 2 Width | 8.000 cm |
| Package 2 Length | 12.000 cm |
| Package 2 Weight | 95.000 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 700 |
| Package 3 Height | 30.000 cm |

| | |
|------------------|-----------|
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 7.120 kg |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|