Eaton ABC-3-R

Catalog Number: ABC-3-R

Eaton ABC series Fast-acting fuse 3A, 250 Vac, 125 Vdc, 32 Vac (self certified), ABC-3-R

General specifications

Product Name Catalog Number

Eaton Bussmann series ABC fast-acting ABC-3-R

fuse

UPC

051712646246

Product Length/Depth Product Height

1.25 in 0.25 in

Product Width Product Weight

0.25 in 0.004 lb

Compliances Catalog Notes

CE Marked Ceramic body allows for higher amp/volt

RoHS Compliant rating combinations.





Product specifications

Fuse indicator

Non-indicating

Interrupt rating

100 AIC at 250 Vac 10 kAIC at 125 Vac/dc

Connection

Ferrule end x ferrule end

Response time

4 hr at 100%, 60 min at 135%, 120 sec at 200%

Quantity

5

Material

Nickel-plated brass endcaps

Ceramic tube

Melting (I2T)

Typical pre-arc: 6.55

Amperage Rating

3 A

Voltage drop

0.14 mV typical

Resistance

0.047 ohms DC cold

Туре

Electronic

Voltage rating

250 Vac, 125 Vdc, 32 Vac (self certified)

Application

Electronic circuits

Resources

PEP Eco-passport

EATO-00033-V01.01-EN

Specifications and datasheets

Eaton Specification Sheet - ABC-3-R

Eaton ABC fast-acting ceramic tube fuses data sheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia