



### Main

Range	Pieno
Product or component type	Switch
Switch application	Panic button
Cover frame colour tint	Lavendar silver

### Complementary

Device mounting	Flush Surface
Wiring device mounting	Flush Surface
Switch function	Switch
Rated current	3 A at 24 V DC
Local signalling	Panic button: push-flat dolly, key reset (red)
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: button Polycarbonate: reset key
Clamping connection capacity	1 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5 mm <sup>2</sup> for stranded cable(s)
Embedding depth	34 mm
Width	87 mm
Height	87 mm
Depth	34 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	75.85 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	455.1 g

Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	5074.8 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------