



### Main

Product or component type	Power socket-outlet
Socket additional information	Shuttered
Load type	Resistive
Cover frame colour tint	Silver bronze

### Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Polycarbonate base Brass metal parts Nylon + GF shutter Polycarbonate cover Steel metal parts
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	29 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Operating altitude	2000 m
Standards	IEC 60884-1
Standards	IEC 60884-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	121.875 g
Package 1 Height	9.5 cm
Package 1 Width	15 cm
Package 1 Length	2.375 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	975 g
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm

Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	9750 g
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>