

## FEATURES

- High pressures and high flow rates
- High quality gaskets
- Class H coils
- Products traceability

# RS PRO Pneumatic Solenoid Valves

RS Stock No.: 2554170



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

*The RS Pro Solenoid valve has simple and compact design, the fluidity solenoid valves are available in 3/2NC versions. The materials used allow the FLUIDITY solenoid valves to be installed also in food applications or in contact with aggressive fluids and reach working temperatures from -40°C to +180°C. The proposed coils allow to obtain high performances and on request low power consumption.*

## General Specifications

Materials	
Body/Sub-Base	Brass

## Electrical Specifications

Supply Voltage	24 V
----------------	------

## Mechanical Specifications

Number of Ports	2/2 NC
Connection	3/4 G female
Connection Size	3/4 in
Operation	Solenoid

## Operation Environment Specifications

<b>Operating Temperature Range</b>	-10°C to +80°C
<b>Minimum Operating Temperature</b>	-20°C
<b>Maximum Operating Temperature</b>	40°C

## Approvals

<b>Standards Met</b>	EN1127, EN80079-36, EN80079-37
<b>Declarations</b>	EU Declaration of Conformity, UE Declaration of Conformity

**CONSTRUCTIONAL/SCHEMATIC DIAGRAMS /ACCESSORIES  
WITH PRODUCT**