



## Main

Range	ZENcolo
Product or component type	Power socket-outlet
Cover frame colour tint	Silver satin
Outlet poles configuration	2P + E

## Complementary

Device mounting	Flush Surface
Switch function	Switch
Colour tint	Silver satin
Rated current	13 A
[Ue] rated operational voltage	250 V AC 50 Hz
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Connections - terminals	Folded terminal
Material	Polycarbonate: base Polycarbonate: grid plate Polycarbonate: surround Phosphor bronze: contact Brass: contact
Height	87 mm
Width	147 mm
Depth	8 mm
Standards	BS 1363-2 MS 589 SS 145

## Environment

Environmental characteristic	UV resistant indoor use
------------------------------	-------------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	206.6 g
Package 1 Height	4 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	3000
Package 2 Weight	774800.0 g
Package 2 Height	105 cm

Package 2 Width	80 cm
Package 2 Length	100 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	980.0 g
Package 3 Height	15 cm
Package 3 Width	19 cm
Package 3 Length	5 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>