



### Main

|                              |                             |
|------------------------------|-----------------------------|
| Range of product             | Ovalis C Series             |
| Product or component type    | Socket-outlet               |
| Device presentation          | Mechanism with fixing frame |
| Socket number                | 1                           |
| Type of packing              | Paint cover                 |
| Number of terminals per pole | 2                           |
| Condition of use             | Indoor                      |

### Complementary

|                                |  |
|--------------------------------|--|
| Device mounting                | Flush  |
| Outlet poles configuration     | 2P + E   |
| Cover type                     | With shutter   |
| Outlet standard description    | Pin earth  |
| Outlet standard                | French   |
| Fixing mode                    | By screws<br>By claws  |
| Colour tint                    | White (RAL 9003)   |
| Surface finish                 | Matt   |
| Rated current                  | 16 A   |
| [Ue] rated operational voltage | 250 V  |
| Network type                   | AC   |
| Network frequency              | 50/60 Hz   |
| Service life in cycles         | 5000 cycles  |
| Electrical durability          | 5000 cycles  |
| Connections - terminals        | Screwless terminals  |
| Shape of screw head            | Pozidriv No 1  |
| Clamping connection capacity   | 1 x 1.5...2 x 4 mm <sup>2</sup> for rigid cable(s)<br>1 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s)<br>1 x 1.5...2 x 4 mm <sup>2</sup> for flexible cable(s) |
| Wire stripping length          | 12 mm  |
| Material                       | ASA + PC: mechanism cover<br>PBT (polybutylene terephthalate) GF30: support frame<br>PC (polycarbonate) GF10 FR: casing  |
| Height                         | 71 mm  |
| Width                          | 71 mm  |
| Depth                          | 44 mm  |
| Embedding depth                | 28 mm  |

|                               |   |
|-------------------------------|---|
| Product weight                | 0.049 kg  |
| Resistance to chemical agents | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|                                       |   |
|---------------------------------------|---|
| Ambient air temperature for storage   | -5...50 °C  |
| Dielectric strength                   | 2000 V  |
| Ambient air temperature for operation | 5...35 °C   |
| Standards                             | NF C 61-314   |
| Product certifications                | LCIE: NF 603415A<br>NF  |
| IK degree of protection               | IK04  |
| IP degree of protection               | IP21D   |
| Environmental characteristic          | Bleach<br>Liquid soap<br>Window-cleaning fluid<br>Alcohol<br>Acetone<br>Oil<br>UV resistant<br>Petrol |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 15 cm    |
| Package 1 Width              | 40 cm    |
| Package 1 Length             | 60 cm    |
| Package 1 Weight             | 5.904 kg |
| Unit Type of Package 2       | P06      |
| Number of Units in Package 2 | 8        |
| Package 2 Height             | 75.0 cm  |
| Package 2 Width              | 60.0 cm  |
| Package 2 Length             | 80.0 cm  |
| Package 2 Weight             | 56.0 kg  |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |