

Double & Three Scissors Lift Table



HT1000



HD1000

• Heavy Duty Design

- Meet EN 1570 norm and ANSI/ASME safety standards.
- These models can be used in above-floor or in-floor pit applications.

Standard Safety Features

- Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- Self lubricating bushings on pivot points.
- Removable lifting eye to facilitate handling and lift table installation.

Model		HD1000	HD2000	HD4000	HT1000	HT2000
Type		double-scissor			three-scissor	
Capacity	(kg)	1000	2000	4000	1000	2000
Lowered Height	(mm)	305	360	400	470	560
Raised Height	(mm)	1780	1780	2050	3000	3000
Platform Size	L x W(mm)	820 x 1300	850 x 1300	1700 x 1200	1700 x 1000	1700 x 1000
Base Frame Size	(mm)	640 x 1240	785 x 1220	1600 x 900	1600 x 1000	1606 x 1010
Lift Time	(sec)	35~45	35~45	55~65	35~45	50~60
Power Pack	(V/Hz/Kw)	380/50, AC 2.2				
Net Weight	(kg)	210	295	520	450	750