


Datasheet

Stock No.





RS PRO 50MM LIGHT MODULE



Led luminous module

DOME	PC
RING	PC
LUMINOUS SOURCE	N°4 LED
AVAILABLE COLOURS	
VOLTAGE	24 Vdc/Vac – 110Vac – 240Vac
OPERATION	∞
CURRENT CONSUMPTION	24 Vac/dc 110Vac 240Vac mA 30 65 55
LIGHT OUTPUT	4 1 1 3 2 1
LIGHT EFFECT	Steady - Flashing
IP RATING	IP66

These data are disclosed only for information purposes. RS Components reserves the right to modify them at any time without prior notice.





OPERATING TEMPERATURE	-30°C+50°C
VIBRATIONS	INDUSTRIAL CEI 60068-2-6 SINE
CERTIFICATIONS, APPROVALS	CE
MOUNTING	Ring
TECHNICAL DRAWING	Ø 48 Ø 55

% \$&, ' , &(J 57#87	
% \$&, ' - &(J 57#87	
% \$&, (\$ &(J 57#87	
% \$&, (% &(J 57#87	
% \$&, (& &(J 57#87	
% \$&, (' &(J 57#87	
% \$&, ()	
%- \$&, (*	
%- \$&, (+ %%\$J 57	
% \$&, (, %\$J 57	
190284-	
1902850	
1902852 &(\$J 57	
1902853 &(\$J 57	
1902854 &(\$J 57	
1902855 &(\$J 57	
1902856 &(\$J 57	
1902857 &(\$J 57	