

Contact Cyanoacrylate Adhesives

CA-Remover



Breaks down and removes all types of cyanoacrylate adhesives

WEICON CA-Remover reliably breaks down and removes all types of cyanoacrylate adhesives. The remover is suitable for cleaning metal parts, tools and many different surfaces that have come into contact with cyanoacrylate adhesives. After a few minutes of soaking in, the dissolved adhesive can be wiped off with a lint-free cloth. In case of stubborn soiling, repeat the procedure. Some plastics, coatings and sensitive surfaces may possibly be damaged by the CA-Remover. Therefore, the material compatibility of the surface should always be tested on a hidden area first. In contrast to other conventional solvents, WEICON CA-Remover is not highly flammable and has a high flash point of $>120^{\circ}\text{C}$.

Technische Daten

Flashpoint	> 120
Gap bridging up to max.	mm mm
Shelf life	12 mon.

Processing

Apply CA-Remover to the area that needs cleaning. After a few minutes of soaking in, the dissolved adhesive can be wiped off with a lint-free cloth. In case of stubborn soiling, repeat the procedure.

Storage

Store in tightly closed original container. Protect from direct sunlight. The storage temperature must not exceed $+50^{\circ}\text{C}$. Keep container in a cool, well-ventilated location. Store in dry place.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

12470030	CA-Remover, 30 ml
12470012	CA-Remover, 12 ml

Conversion table

$(^{\circ}\text{C} \times 1,8) + 32 = ^{\circ}\text{F}$
 $\text{mm}/25,4 = \text{inch}$
 $\mu\text{m}/25,4 = \text{mil}$
 $\text{N} \times 0,225 = \text{lb}$
 $\text{N}/\text{mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$

$\text{Nm} \times 8,851 = \text{lb}\cdot\text{in}$
 $\text{Nm} \times 0,738 = \text{lb}\cdot\text{ft}$
 $\text{Nm} \times 141,62 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$
 $\text{N}/\text{cm} \times 0,571 = \text{lb}/\text{in}$
 $\text{kV}/\text{mm} \times 25,4 = \text{V}/\text{mil}$

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.L. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr