

FEATURES

- Operating temperature range is from - 60 °C to +300°C
- RoHS and REACH compliant
- Silicon free

RS PRO PLUG FOR UNIVERSAL FITTINGS

RS Stock No.: 2312643



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the

leading brands without paying a premium price.

Pneumatic Fitting Accessories



Product Description

The RS PRO plug for universal fittings is made up of brass.

General Specifications

Product Type	Plug Fitting	
Accessory Type	Plug Assembly	
Material	Brass	
Applications	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam, Vacuum	

Mechanical Specifications

Overall Length	10mm
Tube Size	4mm

Operation Environment Specifications

Maximum Temperature	+300°C
Minimum Temperature	-60°C

Pneumatic Fitting Accessories




Approvals

Standards Met	RoHS and REACH Compliant
---------------	--------------------------

Similar Products

Parameters	2312644	2312645
Brand	RS PRO	RS PRO
Product Type	Plug Fitting	Plug Fitting
Accessory Type	Plug Assembly	Plug Assembly
Material	Brass	Brass
Outer Diameter	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam, Vacuum	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam, Vacuum
Overall Length	10.5mm	10.5mm
Tube Size	6mm	8mm
Maximum Temperature	+300°C	+300°C
Minimum Temperature	-60°C	-60°C
Standards Met	RoHS and REACH Compliant	RoHS and REACH Compliant
Applications	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam, Vacuum	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam, Vacuum



Tube	L	Pack.
4	10	50