



(5) Ø0.8(.031) MIN.
MOUNTING HOLE

1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-8 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHMS
- 1.3 VOLTAGE RATING: 250 VOLTS MAX.
- 1.4 VSWR: 1.35 MAX.

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS

3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

4.1 INTERFACE IN ACCORDANCE WITH: BS EN 122340

5.0 ENVIRONMENTAL

5.1 OPERATING TEMPERATURE RANGE: -55° C TO +155° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
4	INSULATION	TEFLON	1	NONE
3	INSULATION	TEFLON	1	NONE
2	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 30µ" MIN.
1	BODY	BRASS	1	GOLD 3µ" MIN.



APPROVED by _____ DATE: _____

DESCRIPTION		MMCX RIGHT ANGLE PCB MOUNT JACK RECEPTACLE							
製圖	DRAWN	TOLERANCE		品名	37-07-8 T.G.G	日期	DATE	版次	REV.
	<i>Kristina</i>	X	±0.2	TITLE	\ROHS COMPLIANT <50Ω	05.14.13'		A-0	
檢圖	CHECK	.XX	±0.1	單位	mm(ln)	DWG.NO. 37-0083			
	<i>Angela</i>	.XXX	±0.05	比例	SCALE				
認定	APPROVAL	ANGLE	±5°	比例	8:1				
	<i>Angela</i>								