







Test Report SL52025257064201TX Date:June 12,2020 Page 1 of 9

XIAMEN DL MEDICAL TECHNOLOGY LTD

ROOM 501, NO. 18, HONGXI SOUTH ROAD, (XIANG'AN) INDUSTRIAL ZONE, XIAMEN TORCH HIGH TECH ZONE ,CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)Face mask

Composition : (A)Melt-blown, Nonwoven

Sample Color : (A)White

Manufacturer : XIAMEN DL MEDICAL TECHNOLOGY LTD

Test Performed : Selected test(s) as requested by applicant

Sample Receiving Date : May 11, 2020

Testing Period : May 11, 2020 - Jun 12, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the


sample(s) tested, for further details, please refer to the following page(s).

Conclusion:

Sample No.	Recommendation Level
(A)	FFP1 NR

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate the except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



SL52025257064201TX

Date:June 12,2020

Page 2 of 9

Test Result

Personal Protective Equipment - Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

EN 149:2001+A1:2009

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination before use.	Comply	Pass

Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.	Comply	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.	Comply	
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer. With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard.	No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



Test Report SL52025257064201TX

Clause 7.8 Finish of Parts

sharp edges or burrs.

(EN 149:2001+A1:2009, Clause 8.2)

Date:June 12,2020 Page 3 of 9

or burrs

,		
Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no	No sharp edges	Pass

Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation value leakage(if exhalation value fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3 and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3	Detail refer to Appendix 1	Meet FFP1, Meet FFP2

Appendix 1: Summarization of Test Data

Inward Leakage Test Data

IIIWaia Lo	anage res	<u>ı Dala</u>						
Subject	Sample	Condition	Walk(%)	Head	Head	Talk(%)	Walk(%)	Mean(%)
	No.			Side/side(%)	up/down(%)			
Zhou	1	A.R.	5.69	5.97	4.34	4.64	5.71	5.27
Luo	2	A.R.	5.98	7.57	5.03	6.64	5.30	6.10
Lu	3	A.R.	4.44	5.33	4.22	5.99	6.03	5.20
Wang	4	A.R.	4.81	4.28	5.40	4.53	4.31	4.67
Bao	5	A.R.	5.15	6.67	7.62	5.90	5.94	6.26
Ding	6	T.C.	6.04	4.44	4.61	5.39	3.78	4.85
Li	7	T.C.	7.37	7.37	6.30	5.57	5.24	6.37
Chen	8	T.C.	5.35	5.34	4.40	6.53	5.11	5.35
Song	9	T.C.	4.37	4.43	5.76	4.84	6.26	5.13
Ye	10	T.C.	5.81	6.69	6.51	6.69	6.26	6.39

Facial Dimension(mm)

Subject	Face length	Face Width	Face Depth	Mouth Width
Chen	125	150	120	58
Lu	115	132	107	48
Zhou	115	135	106	52
Li	125	130	107	46
Luo	125	136	100	43
Zheng	128	140	112	55
Wang	120	147	103	48
Song	120	140	100	50
Bao	130	134	104	50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



Test Re	port SL520	25257064201TX	Date:June 12,202	20 Page 4 of 9
Ding	134	150	110	52
Liu	120	135	117	50
Ye	126	137	105	52

Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

		Test Requirement		Results	Comment	
The	penetration	of the filter of the particle filte	he			
requ	uirements of t	the following table.				
	Classifica	Maximum penetration of test aerosol				
	tion	Sodium chloride test 95	Paraffin oil test 95 l/min			
		l/min			Detail refer to	Meet FFP1
		%	%		Appendix 2	
		max.	max.			
	FFP1	20	20			
	FFP2	6	6			
	FFP3	1	1			

Appendix 2: Summarization of Test Data

Penetration of filter material

Aerosol	Condition	Sample No.	Penetration (%)
		1	1.294
	As received	2	2.310
		3	3.718
		4	2.679
Sodium chloride test	Simulated wearing treatment	5	3.459
		6	3.027
	Mechanical strength +Temperature conditioned	7	4.887
		8	4.937
	Conditioned	9	5.129
		10	6.478
	As received	11	5.703
		12	5.929
		13	6.316
Paraffin oil test	Simulated wearing treatment	14	6.151
		15	6.247
	Machanias I study with Tanana water	16	14.355
	Mechanical strength +Temperature conditioned	17	13.882
	Conditioned	18	13.301
	Flow conditioning: Single fil	ter: 95.0 L/min	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666

f (86-21) 64958763



Test Report SL52025257064201TX Clause 7.10 Compatibility with Skin

/FN 140:2001 : A1:2000 Clause 9.4.9

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Date:June 12,2020	Page 5 of 9
-------------------	-------------

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health.	No irritation or any other adverse effect to health	Pass

Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be of highly flammable nature	Detail refer to	Page
When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame.	Appendix 3	Pass

Appendix 3: Summarization of Test Data

Flammability

- 10:111100 Htg				
Condition	Sample No.	Result		
	1	NIL		
As received	2	NIL		
	3	NIL		
Temperature conditioned	4	NIL		

Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1,0 % (by volume)	Detail refer to Appendix 4	Pass

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Result(%)				
		0.4628				
	1					
As received		0.4632	Mean value:0.46			
AS received	2		iviean value.0.46			
		0.4645				
	3					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3stBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666 f (86–21) 64958763 f (86–21) 64958763



SL52025257064201TX

Date:June 12,2020

Page 6 of 9

Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance	Comply	Pass
tests.		. 455

Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to No exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to No exhalation valve	N.A.
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to No exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to No exhalation valve	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



Test Report SL52025257064201TX Date:June 12,2020 Page 7 of 9

Clause 7.16 Breathing Resistance

(EN 149:2001+A1:2009, Clause 8.9)

	Tes	Results	Comment			
The penetration requirements of						
Classification	Maximi	um permitted resista	ance (mbar)		Datailustanta	Meet FFP1,
	Inl	nalation	Exhalation		Detail refer to	Meet FFP2,
	30 l/min	95 l/min	160 l/min		Appendix 5	Meet FFP3
FFP1	0.6	2.1				
FFP2	0.7	2.4				
FFP3	1.0	3.0	3.0			

Appendix 5: Summarization of Test Data

Breathing resistance (mbar)

	Flavorata (I/asia)				1					2					3		
	Flow rate(l	min)	Α	В	С	D	Е	Α	В	C	D	Е	Α	В	С	D	Е
As received	Inhalation	30	0.2	0.3	0.2	0.3	0.2	0.4	0.3	0.2	0.2	0.3	0.4	0.2	0.2	0.2	0.2
	IIIIaiatioii	95	8.0	0.9	0.8	0.9	0.8	0.9	0.8	0.9	0.8	0.7	8.0	0.9	0.7	0.7	0.7
	Exhalation	160	1.9	2.0	1.9	2.0	1.9	2.0	2.0	1.9	1.9	2.0	2.0	2.0	1.9	1.9	2.0
	Floring (Varia)				4					5					6		
Simulated	Flow rate(l	min)	Α	В	C	D	Е	Α	В	C	D	Е	Α	В	C	D	Е
wearing	Inhalation	30	0.3	0.3	0.3	0.3	0.4	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.4	0.3	0.3
treatment	IIIIaialioii	95	8.0	8.0	0.8	0.8	0.9	0.8	0.8	0.8	0.8	0.8	0.8	8.0	0.9	0.8	8.0
	Exhalation	160	2.2	2.1	2.2	2.1	2.2	2.1	2.2	2.2	2.1	2.2	2.1	2.1	2.2	2.1	2.2
	Ela vala/l	/ ' - \		7			8					9					
	Flow rate(l	min)	Α	В	C	D	Е	Α	В	C	D	Е	Α	В	C	D	Е
Temperature conditioned	Inhalation	30	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	iiiiaialioii	95	0.7	8.0	0.7	0.7	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.7	0.7	0.6	0.6
	Exhalation	160	2.1	2.0	2.1	2.0	2.1	2.0	2.1	2.1	2.0	2.1	2.0	2.0	2.0	2.0	2.0

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86–21) 61402666 f (86–21) 64958763 t (86–21) 61402666 f (86–21) 64958763



SL52025257064201TX

Date:June 12,2020

Page 8 of 9

Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

		Test Requirement	Results	Comment	
Af FF Th flo	Ned particle filt ter clogging the FP1: 4 mbar, FF ne exhalation re w. Neless particle ter clogging the	eathing resistance tering half masks: inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb filtering half masks: inhalation and exhalation resisives: FP2: 4 mbar, FFP3: 5 mbar at 95	Optional for single shift device only	N.A.	
Al	types (valved eet the clogging	netration of filter material and valveless) of particle filter requirement shall also meet the			
	Classificatio	Maximum penetration		Optional for single	
	n	Sodium chloride test 95 l/min	shift device only	N.A.	
		%			
	EED4	max.			
	FFP1	20	20		
	FFP2	6	6		
	FFP3	1	1		

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured,	No demountable	N.A.
where possible by hand	parts	IV.A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52025257064201TX

Date:June 12,2020

Page 9 of 9





The statement of conformity in this test report is only based on measured values by the laboratory and does not take their uncertainties into consideration.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763