



### Main

Range	Pieno
Product or component type	Fused connection unit
Rated current	13 A at 250 V AC 50 Hz
Load type	Resistive
Protection type	Fuse
Number of gangs	1 gang
Cover frame colour tint	Lavender silver

### Complementary

Wiring device mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Clamping connection capacity	1 x 2.5 mm <sup>2</sup> for solid cable(s) 2 x 4 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Folded terminal
Width	87 mm
Height	87 mm
Depth	27.8 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS 1363

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.78 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	103.03 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.03 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	11887.6 g

## Offer Sustainability

---

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---