

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON UW Hardener

Code-Nr. 104402

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Skin Sens. 1B H317 Aquatic Chronic 3 H412

Hazard Statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements



No. 1907/2006 (REACH) Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

Signal word

Warning

Hazard Statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261 P264 P272 P273 P280	Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/eye protection.
P302 + P352 P305 + P351 + P338 P312 P333 + P313 P362 + P364	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor/if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl] propoxy] propan-1-ol; 3-sulfanylpropane-1,2-diol, 3,6-diazaoctanethylenediamin

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
112-24-3	203-950-6	3,6-diazaoctanethylenediamin	< 1	Acute Tox. 4, H312 / Skin Corr. 1B, H314 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412
14807-96-6	238-877-9	talcum (Mg3H2(SiO3)4)	1 - 5	
13463-67-7	236-675-5	titanium-dioxide	5 <= 10	
90-72-2	202-013-9	2,4,6-Tri-(dimethylaminomethyl)phenol	<= 4,9	Acute Tox. 4, H302 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Acute Tox. 4, H312



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

	ingredients ((vontinuou)		
CAS No	EC No	Name [%	% eight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
1477-55-0	216-032-5	m-Phenylenbis (methylamine)	= 2,4	Acute Tox. 4, H302 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319
72244-98-5	615-735-8	3-[3-(3-hydroxypropoxy)-2,2-bis[(3- 50 hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	0 <= 75	Skin Sens. 1B, H317 / Aquatic Chronic 3, H412
REACH				
CAS No	Name			REACH registration number
112-24-3	3,6-diazaocta	anethylenediamin		not subject to registration
14807-96-6	talcum (Mg3	H2(SiO3)4)		01-2120140278-58
13463-67-7	titanium-diox	ide		01-2119489379-17
	2,4,6-Tri-(din	nethylaminomethyl)phenol		01-2119560597-27
90-72-2				
90-72-2 1477-55-0	m-Phenylenk	ois (methylamine)		01-2119480150-50

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth thoroughly with water.

Give plenty of water to drink in small sips.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

5.2. Special hazards arising from the substance or mixture

Metal oxides

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

Sulfur oxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Avoid dust formation.

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Do not inhale dust.

Ensure sufficient ventilation.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Store at +5 till +25 °C.

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1314-56-3	Diphosphorus pentoxide	8 hours Short-term	2		EH40/2005
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005
13463-67-7	Titanium dioxide: total inhalable dust	8 hours	10		EH40/2005
13463-67-7	Titanium dioxide: respirable dust	8 hours	4		EH40/2005

DNEL-/PNEC-values

DNEL worker

90-72-2

DNEL worke	r			
CAS No	Substance name	Value	Code	Remark
13463-67-7	titanium-dioxide	10 mg/m3	DNEL long-term inhalative (systemic)	
90-72-2	2,4,6-Tri-(dimethylaminomethyl)phenol	0,2 mg/kg bw/day	DNEL long-term dermal (systemic)	
		0,31 mg/m3	DNEL long-term inhalative (systemic)	
PNEC				
CAS No	Substance name	Value	Code	Remark
13463-67-7	titanium-dioxide	100 mg/l	PNEC sewage treatment plant (STP)
		1 mg/l	PNEC aquatic, marine water	

PNEC sediment, marine water

PNEC sediment, freshwater

PNEC aquatic, freshwater

PNEC aquatic, freshwater

PNEC sewage treatment plant (STP)

1000 mg/kg

100 mg/kg

0,127 mg/l

0,084 mg/l

0,2 mg/l

2,4,6-Tri-(dimethylaminomethyl)phenol



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

DNEL-/PNEC-values (continued)

CAS No Substance name Value Code Remark

0,0084 mg/l PNEC aquatic, marine water

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, filter AX

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourpastycreamsulphur-like

Odour threshold not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	not determined				
melting point	not determined				
Flash point	not applicable				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

	Value	Temperature	at	Method	Remark
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	1,421 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient noctanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Oxidising properties No information available.					
Explosive properties not determined					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

Metaloxides



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg			ATE
LD50 acute dermal	> 2000 mg/kg			ATE
LC50 acute inhalation	> 20 mg/l ()			ATE
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

Value

Mutagenicity	No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity	No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity	No indications of carcinogenic effects are available from long-term trials.

Method

Validation

Species

Experiences made from practice

Sensitization through skin contact possible.

Frequent contact specially if dried out may cause skin and eye irritations.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

	Value	Species	Method	Validation	
Algae	EC50 3700 Mikro-g/l (96 h)	Pseudokirchneriella subcapitata		CAS: 112-24-3	_

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Slight bioaccumulation potential.

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

08 04 10 15 01 02 waste adhesives and sealants other than those mentioned in 08 04 09

plastic packaging

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	s -	-	_



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 21.09.2018 (GB) Version 2.7

WEICON UW Hardener

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 2.6

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.