


RS Pro Datasheet

2.5mm Pitch Screwless Terminal Blocks

- Interlocking modules
- 45° degree cable entry
- Lever actuator cable release
- Moulded in UL94-V0 flame retardant PA66
- 0.5mm² (28-20AWG) solid cable
-  approved

CSTBP45VC



SPECIFICATION

Rating	UL=4A/300V
Insulation resistance	500MΩ/500V
Withstand Voltage	AC2000V/1min
Contact Resistance	20mΩ (max)
Working Temperature	-40°C to 105+°C
Mouldings	UL94-V0 Flame retardant PA66
Spring Clamp	Phosphor chrome tin plated
Recommended PCB hole size	ø1.1mm

TYPE NO.	POLES	LENGTH
CSTBP45VC/2	2	6.5mm
CSTBP45VC/3	3	9.0mm
CSTBP45VC/4	4	11.5mm
CSTBP45VC/5	5	14.0mm
CSTBP45VC/6	6	16.5mm
CSTBP45VC/7	7	19.0mm
CSTBP45VC/8	8	21.5mm
CSTBP45VC/9	9	24.0mm
CSTBP45VC/10	10	26.0mm
CSTBP45VC/11	11	29.0mm
CSTBP45VC/12	12	31.5mm

