



Main

Range	Vivace
Product or component type	Switch
Device short name	KB34
Device application	Lighting
Switch function	1-way

Complementary

Device presentation	Complete mechanism
Actuator	Rocker
Number of gangs	4 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base Polycarbonate: dolly Nylon: actuator Silver plated copper: bridge Brass: terminal cover
Surface finish	Glossy
Surface treatment	Untreated
Type of packing	Box
Quantity per set	8
Sale per indivisible quantity	1
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Embedding depth	24 mm
Rated current	10 AX at 250 V AC, inductive 10 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	8 screw terminals
Terminal identifier	COM L1 L2
Tightening torque	0.4 N.m
Clamping connection capacity	$\leq 2 \times 2.5 \text{ mm}^2$ for rigid or stranded cable(s)
Wire stripping length	12 mm
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un
Width	86 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Height	86 mm
Depth	36.5 mm
Net weight	0.0829 kg

Environment

Standards	IEC 60669
Product certifications	SNI[RETURN]SIRIM
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	2.4 cm
Package 1 Length	8.6 cm
Package 1 Weight	85 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations