

AP7920B

APC NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord



Overview

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
Lead time	Usually in Stock

Main

Colour	Black
PDU type	Switched
Cable length	1.98 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

Complementary

Main Input Voltage	200 V 208 V 230 V
Height	4.4 cm
Width	44.5 cm
Main Output Voltage	208 V 230 V
Depth	10.8 cm
Net weight	2.27 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Connection Type	IEC 60320 C14
Mounting mode	Rack-mounted
Number of rack unit	1U
Mounting position	Horizontal
[In] rated current	12 A
Permissible voltage	200...240 V
Input current limits	15 A
Load capacity	2300 VA
Rated current	10 A - 230 V 12 A - 208 V
Network frequency	50/60 Hz
Number of power socket outlets	8 IEC 60320 C13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.


Environment

Product certifications	cUL listed[RETURN]CE[RETURN]CSA[RETURN]GOST[RETURN]IRAM[RETURN]UL listed[RETURN]VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	34.3 cm
Package 1 Length	47 cm
Package 1 Weight	3.45 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------