

FEATURES

- **Body material 16 SWG mild steel**
- **Steel construction gives long life and reliability**
- **Hands free control**
- **Robust and compact design construction**
- **Sealed to IPX2**
- **Supplied with 2m of 3mm bore PVC tubing**
- **Weight 0.25g (approx.)**
- **Operating temperature range - 10°C to 40°C**
- **Dimensions: 66W x 90L x 24H**

RS PRO Foot Switch - 16 SWG Mild Steel Case Material

RS Stock No.: 170-806



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description ATTRIBUTE 1

RS PRO mild steel foot actuator foot switch in a powder grey finish with a black polypropylene tread. Similar to the shape of the electric footswitch this compact and tough foot actuator is ideal for foot operated air switching systems.

This foot actuator foot switch is suitable for use with various air switches. Air Switches can be purchased separately, please view - [316-951](#), [319-708](#), [319-714](#), [319-720](#), [319-736](#), [319-742](#), [319-758](#).

General Specifications

Case Material	16 SWG Mild Steel
Guard Cover	No
Colour	Black, Grey
Applications	Foot switches are commonly used in applications where hands-free control is more practical or safer. They can be found on: Industrial machinery and smaller power tools, Hospital beds, Dentist Chairs, Lamps
Accessory Type	Actuator
For Use With	Air Operated Switch

Mechanical Specifications

Length	90mm
Height	24mm
Dimensions	66mm x 90mm x 24mm
Width	66mm
Weight	0.25g (approx.)

Operation Environment Specifications

Operating Temperature	-10°C to 40°C
-----------------------	---------------

Protection Category

IP Rating	IPX2/IPX7
-----------	-----------

Approvals

Standards Met	2014/35/EU; EN 60950; EN 61058-2- 1; EN 61058
Compliance/Certifications	RoHS



