

WEPBA 17-150 Quick RT (601098000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box



Product may differ from image



- Maximum productivity thanks to top performance with low weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest degree of user safety thanks to patented, mechanical disc brake and deadman's switch: disc stop in 2 seconds after releasing even in case of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

Disc-Ø	150 mm // 6 "
Rated input power	1750 W
Output power	1070 W
No-load speed	9600 rpm
Speed at rated load	9600 rpm
Torque	4.4 Nm / 39 in-lbs
Spindle thread	M 14
Handle circumference	138 mm / 5.438 "
Weight (without power cable)	2.8 kg / 6 lbs
Cable length	4 m / 13 ft

Vibration

Surface grinding	6 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	4.9 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard
 Metabo VibraTech (MVT) side handle
 Inner support flange
 M-Quick flange nut