

FEATURES

- Power OFF delay
- 22.5mm width
- DIN Rail mounting
- DPCO output relay
- 0.6s to 600s timing range
- LED indication for power and relay status
- 24V-240V ac/dc supply voltage
- IP20 (terminals), IP40 (enclosure) protection

RS PRO DPDT Timer Relay - 0.6 → 600 s, 2 Contacts, True Off Delay, DIN Rail

RS Stock No.: 896-6844



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS Pro True Off delay time delay relay is a multi-voltage, multi-range timer that is compact in size and suitable for DIN Rail mounting.

General Specifications

Switch Configuration	DPCO
Mode of Operation	True Off Delay
Contact Configuration	2CO
Number of Timer Functions	Single
Number of Contacts	2
Time Range	0.6s to 600s
Time Increment	Seconds
Applications	Textiles, Chemical industry, Mining, Irrigation, Raw material handling, Food and beverages, Industrial process control

Electrical Specifications

Power Supply	External
Supply Voltage	24V to 240V ac/dc
Minimum Voltage	24VAC/DC
Maximum Voltage	240VAC/DC
Current Maximum	5A
Current Minimum	0.1A
Relay Output	DPCO
Terminal Type	Screw

Mechanical Specifications

Mounting Type	DIN-Rail
Depth	100.5 mm
Width	22.5 mm
Length	75 mm

Operation Environment Specifications

Maximum Operating Temperature	60°C
Minimum Operating Temperature	-15°C

Protection Category

IP Rating	IP20; IP40
------------------	------------

Approvals

Compliance/Certifications	CE, RoHS
----------------------------------	----------

