

## Datasheet

**RS Pro Insulated Crimp Piggyback Terminal, 6.35 x 0.8mm, 0.5mm<sup>2</sup> to 1.5mm<sup>2</sup>, 22AWG to 16AWG, Red**  
RS Stock No: **534-367**



## Product Details

RS Pro insulated crimp piggyback terminal in red colour, has 6.35 x 0.8 mm tab size and 0.5 mm<sup>2</sup> to 1.5 mm<sup>2</sup>, 22 AWG to 16 AWG wire size. It has a range of insulated piggyback crimp terminals with a copper sleeved barrel and nylon or flared vinyl insulation. This insulated piggyback crimp wire connector is colour coded for use with different wire sizes and accept a variety of tab dimensions.

## Features and Benefits

- Insulated piggyback crimp terminals with a copper sleeved barrel with nylon or flared vinyl insulation
- Insulated piggyback crimp wire connectors are colour coded for use with different wire sizes and accept a variety of tab dimensions
- Red 0.5 - 1.0 mm<sup>2</sup>, blue 1.5 - 2.5 mm<sup>2</sup> and yellow 2.5 - 6.5 mm<sup>2</sup>

**Specifications:**

Colour	Red
Contact Material	Brass
Contact Plating	Tin
Insulation	Insulated
Insulation Material	Vinyl
Shrouded	Unshrouded
Maximum Wire Size (AWG)	16 AWG
Maximum Wire Size (mm <sup>2</sup> )	1.5 mm <sup>2</sup>
Minimum Wire Size (AWG)	22 AWG
Minimum Wire Size (mm <sup>2</sup> )	0.5 mm <sup>2</sup>
Overall Length	20 mm
Tab Size	6.35 x 0.8 mm
Tab Thickness	0.8 mm
Tab Width	6.35 mm
Wire Size	22 to 16 AWG
Current Rating	10 A
Temperature Rating	+75°C
Voltage Rating	300 V