

FEATURES

- 10 A (continuous) current range
- Data hold/relative modes
- 1 MHz counter with full 9999 Count display
- Diode test and continuity sounder
- 4 nF to 40 μF capacitance ranges
- Mains proof resistance ranges
- Full autoranging with manual override
- Auto power shutdown
- Digital display update rate 2 per second
- Bargraph display update rate 20 per second
- Fused 400 mA and 10A ranges
- Dust and water protected to IP64
- Water resistant via O-Ring sealed case
- Dual high energy fuse protection
- AC Coupled AC conversion true RMS responding to the RMS sine wave input
- 3 years warranty

RS PRO Digital Multimeters- IDM106N Handheld Digital Multimeter

RS Stock No.: 123-3236



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

RS PRO IDM106N RMS Digital Multimeter

RS PRO IDM106N offers high specification performance with 4000 count display and 42 segment bar graph. These handheld devices can measure capacitance, voltage, electrical current, frequency, peak hold, temperature and resistance with diode and continuity check. This meter has an LCD display where the measurement readouts can be viewed.

General Specifications

Multimeter Type	Handheld
Function Measured	AC Current, AC Voltage, Capacitance, Continuity, DC Current, DC Voltage, Diode Test, Frequency, Peak Hold, Resistance, Temperature
True RMS	Yes
Display Type	LCD
Bar graph	42 segments
Operating Temperature (Min to Max)	0 to +50°C
Storage Temperature (Min to Max)	-20°C to +60°C
Diode Test	Yes
Continuity Test	Yes
Auto power off	Yes,Approx 30 minutes
Optical isolated interface output	RS232

Measurement

Туре	Absolute Maximum Measurement	Resolution	Best Accuracy
DC Current	10A dc	10μΑ	±0.4% + 2 Digits
AC Current	10A ac	10μΑ	±1.5% + 5 Digits
Resistance	40ΜΩ	100mΩ	±0.4% + 2 Digits
DC Voltage	1000 V dc	100μV dc	±0.1% + 2 Digits
AC Voltage	1000V ac	0.1mV ac	±1.5% + 5 Digits
Capacitance	40mF	1pF	±2% + 8 Digits
Frequency	400 MHz		

Electrical Specifications

Battery Type	IEC 6F22, JIS 006P, NEDA 1604, 9V
Battery life	300 h
Safety Category Voltage	600 V, 1000 V



Mechanical Specifications

Dimensions	100 x 55 x 212 (with Holster)mm	
Width	55mm	
Length	100mm	
Height	212mm	
Weight	620g	

Protection Category

Safety Category Level CAT II, CAT III

Approvals

Compliance/Certifications	IEC / CSA
Declarations	RoHS Certificate of Compliance

Similar Products

Stock No.	Brand	Product	Multimeter	Functions	Digit
		Name	Type	Measured	Resolution
124-2010	RS PRO	IDM505	Handheld	AC Current,	
		Handheld		AC Voltage,	
		Digital		Capacitance,	
		Multimeter		Continuity,	
		With RSCAL		DC Current,	
		calibration		DC Voltage,	
				Diode, Duty	
				Cycle,	
				Frequency,	
				Resistance,	
				Temperature	
161-1629	RS PRO	Handheld	Handheld	AC Current,	
		Digital		AC Voltage,	
		Multimeter		Capacitance,	
				DC Current,	
				DC Voltage,	
				Frequency,	
				Resistance	

Physical Dimensions / Connection Diagram / Accessories Included

Digital Multimeters

