M12 Sensor Connector D-Coded, Field-wireable



Field-wireable connector M12, D-coding, Male, Straight

RoHS **Compliant**



Features

- Metal coupling nut
- Metal housing
- Protection class: IP67
- Screw terminal
- 4-Pin
- Cable feedthrough 6mm to 8mm
- PG9 screw-in thread

Technical Data Contact assignment

Connector

Connector A : Male, M12 x 1, Straight, D-coded

Number of Pins

: Brass, Gold-plated Contacts

: PBT **Contact Carriers**

Copling Nut/screw : Brass, Nickel-plated Connector body : Brass, Nickel-plated External diameter of the cable : 6mm to 8mm (PG 9) Core cross-section/Clamping ability : 0.2 to 0.75mm² Connection mode : Screw connection Mechanical lifespan : ≥100 Mating cycles

Pollution degree

Protection Class : IP67, (screwed together)

Locking mode : Screw Standard : IEC 61076-2

Electrical properties at +20 °C


Rated Voltage : 250V Current :4A Insulation resistance : ≥108Ω Forward resistance : ≤ 3mΩ Test voltage : 2500V

Mechanical and chemical properties

: -25°C to 85°C Ambient temperature range



Diagram



Dimensions: Millimetres

Part Number Table

Description	Part Number
M12 Sensor Male Connector, D-Coded, 4 Pins	MP011267

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

