

NSYTBS16128

ABS box IP66 IK07 RAL7035
Int.H150W105D80 Ext.H164W121D87 Opaque
cover H20



Main

| | |
|---------------------|--|
| Range | Thalassa |
| Product name | Thalassa TBS |
| Device application | Multi-purpose |
| Category | Industrial box |
| Height | 164 mm |
| Width | 121 mm |
| Depth | 87 mm |
| Internal height | 150 mm |
| Internal width | 105 mm |
| Internal depth | 80 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 1 body 1 cover 4 cover screw |
| Quantity per set | Set of 2 |
| Body type | One piece moulded |
| Type of front cover | Low plain cover |
| Cover fixing | Plastic screws |
| Lock type | Captive screw flat outside sealed area |
| Removable parts | Cover by captive screws |

Complementary

| | |
|-------------------------------------|---------------------------------------|
| Material | ABS (acrylonitrile butadiene-styrene) |
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 |
| Product certifications | TÜV |
| Electrical insulation class | Class II |
| IP degree of protection | IP66 conforming to NEMA 4.4X |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Glow wire resistance | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C |
| Operating temperature | -25...60 °C |
| Product weight | 0.32 kg |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.7 cm |
| Package 1 Width | 12.1 cm |
| Package 1 Length | 16.4 cm |
| Package 1 Weight | 320 g |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|