



Product Datasheet

**RS- 1806816**

**Premier Safety Lockout Padlock  
Standard Steel Shackle - Key Different  
(ES - PLSP 6 - S - KD - BLUE)**





### **Standard features:**

- Each padlock is supplied with 1 key.
- Chrome plated Steel Shackle for better corrosive resistance of 5 mm for best physical strength.
- Resistant to extreme temperature changes – 13<sup>0</sup> F to + 194<sup>0</sup> F.
- Compact for easy carrying and storage.
- Light weight, solid Aluminium core Safety Padlock
- Made especially for Lockout / Tagout Applications
- Automatic locking for user convenience
- 6 pin brass cylinder
- Insulated body, resistant against heat, dust and debris.
- Compliant with regulations : 1 employee = 1 padlock = 1 key (OSHA).
- Logo printing / Laser engraving optional (front, back, left and right side).
- Key retaining feature (when shackle is open).
- The solid aluminum body is encased by a colored plastic cover for easy identification. To further improve visibility and identification,
- Body and shackle insulated against electric shock

### **Technical data**

- Comes with 5 mm thick x 46 mm steel shackle
- Weight around : 97 grams
- Specified for Lockout / Tagout purpose internationally

### **Package includes:**

- Packed single unit in cardboard box.